

SECURITY ALARM CABLE

SHIELDED

CMP/FT6 Rated, FPLP, CL2P, CL3P



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

PART NO.	AWG/COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
			INCH	mm	INCH	mm	
22 AWG							
982202SD	22/2	SOL	.018	.457	.125	3.18	13
912202SD	22/2	7	.018	.457	.132	3.35	13
982204SD	22/4	SOL	.018	.457	.126	3.20	20
912204SD	22/4	7	.018	.457	.150	3.81	20
912206SD	22/6	7	.018	.457	.178	4.52	26
912208SD	22/8	7	.018	.457	.193	4.90	37
912210SD	22/10	7	.018	.457	.197	5.00	42
912212SD	22/12	7	.018	.457	.212	5.38	46
20 AWG							
912002SD	20/2	7	.018	.457	.145	3.68	17
912004SD	20/4	7	.018	.457	.167	4.24	27
18 AWG							
911802SD	18/2	7	.018	.457	.162	4.11	23
911803SD	18/3	7	.018	.457	.175	4.45	30
911804SD	18/4	7	.018	.457	.191	4.85	37
911806SD	18/6	7	.018	.457	.229	5.82	56
911808SD	18/8	7	.018	.457	.259	6.58	66
911809SD	18/9	7	.018	.457	.269	6.83	73
911812SD	18/12	7	.018	.457	.309	7.85	99
16 AWG							
911602SD	16/2	19	.018	.457	.187	4.75	33
911603SD	16/3	19	.018	.457	.198	5.03	45
911604SD	16/4	19	.018	.457	.218	5.54	59
14 AWG							
911402SD	14/2	19	.018	.457	.229	5.82	54
911403SD	14/3	19	.018	.457	.243	6.17	70
911404SD	14/4	19	.018	.457	.264	6.71	86
12 AWG							
911202SD	12/2	19	.018	.457	.263	6.68	68
911204SD	12/4	19	.018	.457	.303	7.70	121

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted, aluminum mylar shielding with drain wire and an overall low smoke white PVC jacket* with rip cord.

*Other colors available upon request. Please consult factory for minimums and lead times.

SPECIFICATIONS

Conductor	Bare Copper
Insulation	Low Smoke PVC
22 AWG	.007" PVC
20 AWG	.008" PVC
18 AWG	.009" PVC
16 AWG	.010" PVC
14-12 AWG	.012" PVC
Jacket	Low Smoke PVC
Shield	Aluminum Mylar

NEC Articles

22-16 AWG: FPLP/760, CMP/800, CL3P, CL2P/725
14 AWG-12 AWG: FPLP, CL3P

Voltage Rating 300 V

Temp. Rating 75°C

Drain Wire 22-20 AWG: 26 AWG
18-12 AWG: 24 AWG

APPLICATIONS

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC SHIELDED (ETL)us TYPE CL3P/FPLP
c(ETL)us TYPE CMP 3054355

*14-12 AWG are not recognized by c(UL) or c(ETL).



The information contained on this specification is intended to be used as a guide in product selection and is believed to be reliable. ADC has made every effort to ensure the data shown above is accurate at the time of publication. This specification is subject to change anytime without notice. Rev EC0413

PHONE: (800) 343 2579 • FAX: (828) 389 3922 • WWW.ADCABLE.COM

SECURITY ALARM CABLES