CATV COAXIAL CABLES PVC

CATV, CATVR, CMR, CM



RoHS Compliant



Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

by outside	Stariuarus U	rgariizations ii	icidaling (C(OL)us	and c(ETLJUS.	
PART NO.	ТҮРЕ	SHIELD	AWG	NOMINAL OD (INCH)		NEC TYPE	SHIP WT /
				CORE	CABLE		1M'
RG 59							
4-4590	RG 59	Foil + 45% AL	20 BCCS	.140	.240	CATV CM	25.01
4-4599	RG 59	Foil + 53% AL	22 BCCS	.140	.240	CATV	24.62
4-4591	RG 59	Foil + 65% AL	20 BCCS	.146	.242	CATV	25.89
RG 6							
4-4069	RG 6	Foil + 40% AL	18 BCCS	.180	.270	CATV	29.29
4-4061	RG 6	Foil + 60% AL	18 BCCS	.180	.270	CATV CM	29.85
4-4061R	RG 6 Riser	Foil + 60% AL	18 BCCS	.180	.270	CATVR CMR	29.85
4-4061M	RG 6 w/Mess	Foil + 60% AL	18 BCCS	.180	.270 x.401	CATV CM	47.83
4-4061D	RG 6 Dual	Foil + 60% AL	18 BCCS x 2	.180	.270 x .570	CATV	62.70
4-4061DM	RG 6 Dual w/Mess	Foil + 60% AL	18 BCCS x 2	.180	.270 x .703	CATV	75.63
4-4061QS	RG 6 Quad	Foil + 60% AL Foil + 40% AL	18 BCCS	.180	.298	CATV CM	35.30
4-4068**	RG 6	Foil + 60% AL	18 BC	.180	.270	CATV	28.32
4-4068QS**	RG 6 Quad	Foil + 60% AL Foil + 40% AL	18 BC	.180	.300	CATV	36.21
4-4060	RG 6	Foil + 90% AL	18 BCCS	.180	.270	CATV CM	28.40
		R	G 11				
4-4011QS	RG 11 Quad	Foil + 60% AL Foil + 40% AL	14 BC	.280	.430	СМ	65.14
4-4111	RG 11	Foil + 65% AL	14 BCCS	.280	.405	СМ	66.27
4-4111QS	RG 11 Quad	Foil + 60% AL	14 BCCS	.280	.430	СМ	73.0

Foil + 40% AL

PRODUCT DESCRIPTION

Foamed dialectric core over solid copper or copper covered steel center conductor, bonded aluminum foil, aluminum braid shield, overall black PVC jacket*.

- * Other colors available upon request. Please consult factory for minimums and lead times.
- * Riser rated/FT4 available upon request

SPECIFICATIONS

Nominal Impedance 75 Ohm
Nominal Velocity of Propagation 82
Nominal Capacitance 16.2
NEC Articles: CATV, CATVR, CMR, CM
Temp. Rating 75°C
Sunlight Resistant
RoHS Compliant
Attenuation see chart on page 48
(RG6 & RG11 are 3GHz swept tested)

APPLICATIONS

- Audio/Video
- CATV

AVAILABLE PUT-UPS

1,000' Reels and Boxes 500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

RG X XX AWG (ETL)us TYPE YYYY c(ETL)us TYPE CM 3054355







^{**}Non Bonded Aluminum Tape Shield.

