

QuickPort™ Fiber Optic Adapters ST, SC, LC, and MTP™

APPLICATION

QuickPort Fiber Optic Adapters provide connectivity for workstation cabling termination on single-mode and multimode fiber cable. QuickPort bulkhead modules snap into any housing with the QuickPort name: flush- and surface-mount outlets, Multimedia Outlet System (with adapter), patch panels, and patch blocks.



SPECIFICATION

QuickPort Fiber Optic Adapters for fiber optic cabling media shall be individual snap-in style and shall fit into QuickPort panels. The LC, SC, and ST Adapters shall be compatible with single-mode, multimode, and laser-optimized multimode connectors, and available in zirconia ceramic or phosphor bronze sleeves. LC shuttered adapters shall be IP5x-rated, and shall open and close automatically with the insertion and removal of an LC connector.

DESIGN CONSIDERATIONS

- QuickPort adapters snap into QuickPort panels or modules
- ST and SC QuickPort Adapters are available in standard colors of ivory, white, gray, and black
- Internal patented shutters on LC adapters eliminate the need for dust plugs to reduce waste, speed deployment, and ensure safer installation
- Shuttered LC adapter door will illuminate when a VFL is used for fiber traceability
- Shuttered LC adapter is IP5x-rated for limited protection against dust ingress
- Use in permanent or temporary applications
- ST, SC, and LC QuickPort Adapters are available with zirconia ceramic or phosphor bronze sleeves, and are compatible with single-mode, multimode, and laser optimized (LC only)
- MTP Adapter key up to key down for single-mode applications

STANDARDS COMPLIANCE

- ANSI/TIA-568.3-D for performance requirements
- ANSI/TIA-604-2 (ST), -38 (SC), -5 (MTP), -10B (LC) for connector intermateability
- IEC 60529 IP5x dust protection (LC)

PHYSICAL SPECIFICATIONS

Dimensions: See page two

Materials:

QuickPort Housing	Snap-in module bodies are high-impact, fire-retardant plastic rated UL 94V-0
ST Fiber Adapter	Single-mode: zirconia ceramic sleeve Multimode: phosphor bronze sleeve
SC Fiber Adapter	Single-mode: zirconia ceramic sleeve Multimode: phosphor bronze sleeve
LC Fiber Adapter	Single-mode: zirconia ceramic sleeve LOMM: zirconia ceramic sleeve Multimode: zirconia ceramic sleeve

WARRANTY INFORMATION

For a copy of Leviton product warranties, visit www.leviton.com.

ELECTRONIC FILES

For CAD files, typical specs, or dimensional line art (.DXF, .DWG), visit www.leviton.com.

41084-xxx, 41085-xxx, 41086-xxx

Leviton Network Solutions

2222 - 222nd St. SE
Bothell, WA 98021-4416

tel 1-800-824-3005
tel +1-425-486-2222
appeng@leviton.com
www.leviton.com

Asia / Pacific
T +1.631.812.6228
E infoasean@leviton.com

Europe
T +44.0.1592.772124
E customerserviceeu@leviton.com

Canada
T +1.514.954.1840
E pcservice@leviton.com

Mexico
T +52.55.5082.1040
E lsmarketing@leviton.com






Caribbean
T +1.954.593.1896
E infocaribbean@leviton.com

Middle East & Africa
T +971.4.247.9800
E lmeinfo@leviton.com

China
T +852.2774.9876
E infochina@leviton.com

South Korea
T +82.2.3273.9963
E infokorea@leviton.com

Colombia
T +57.1.743.6045
E infocolombia@leviton.com



QUICKPORT FIBER ADAPTERS ^

DESCRIPTION	PART NO.
QuickPort Duplex LC shuttered, MM, zirconia ceramic sleeve, beige	41086-ML*
QuickPort Duplex LC shuttered, 10G LOMM, zirconia ceramic sleeve, aqua	41086-LL*
QuickPort Duplex LC shuttered, SM, zirconia ceramic sleeve, blue	41086-SL*
QuickPort Simplex SC shuttered, MM, phosphor bronze sleeve, female front/back	41085-M°C
QuickPort Simplex SC shuttered, SM, zirconia ceramic sleeve, female front/back	41085-S°C
QuickPort Simplex SC/APC, SM, zirconia ceramic sleeve, female front/back	41085-AS°
QuickPort ST, MM, phosphor bronze sleeve	41084-S°F
QuickPort ST, SM, zirconia ceramic sleeve	41084-S°Z
QuickPort MTP®, SM/MM, key up to key down (opposed)	41085-TP†
QuickPort MTP, MM, key up to key up (aligned)	41085-TB†

* = Colors: Ivory (I), White (W), Gray (G), Black (E), Yellow (Y), Red (R), Blue (L), Green (V), Orange (O)
 ° = Colors: Ivory (I), White (W), Gray (G), Black (E)
 † = Colors: White (W), Black (E)
 ^ Minimum order quantity and lead times may apply.



Leviton Network Solutions

2222 - 222nd St. SE
Bothell, WA 98021-4416

Asia / Pacific
T +1.631.812.6228
E infoasian@leviton.com

Canada
T +1.514.954.1840
E pcservice@leviton.com

Caribbean
T +1.954.593.1896
E infocaribbean@leviton.com

China
T +852.2774.9876
E infochina@leviton.com

Colombia
T +57.1.743.6045
E infocolombia@leviton.com

tel 1-800-824-3005
tel +1-425-486-2222
appeng@leviton.com
www.leviton.com

Europe
T +44.0.1592.772124
E customerserviceeu@leviton.com

Mexico
T +52.55.5082.1040
E lsamarketing@leviton.com

Middle East & Africa
T +971.4.247.9800
E lmeinfo@leviton.com

South Korea
T +82.2.3273.9963
E infokorea@leviton.com